

Model	LTES08
Type	Back opening
Atmospheric Pressure	80 kPa to 106 kPa
Operating Ambient Temperature	0 °C to 250 °C (32 °F to 482 °F)
Relative Humidity	5 % to 95 % noncondensing
Protection Rating	IP66, NEMA-4X enclosure rating
Input Power	-
Inlet Water Temperature	< 35 °C
Water Flow Rate	0.3 to 0.6 liter per second
Inlet Water Pressure	0.1 Mpa
Dust Air Pressure	0.1 Mpa to 0.4 Mpa
Air Flow Rate	0.3 to 0.6 liter per second
Water Inlet/Outlet	G-3/4" thread, 20 mm inner diameter
Dimensions (W × H × L)	139 mm × 183 mm × 375 mm (5.47 in × 7.20 in × 14.76 in)
Internal Usable Size (W × H × L)	90 mm × 80 mm × 280 mm (3.54 in × 3.15 in × 11.02 in)
Window Thickness	8 mm (0.31 in)
Window Viewing Area (Ø)	70 mm (2.76 in)
Weight	<ul style="list-style-type: none"> <li>○ 9.5 kg (20.94 lb)</li> <li>○ 11.4 kg (25.13 lb) (wall mount bracket included)</li> </ul>
Material	AISI 304 stainless steel
Cable Outlet	G-3/4" × 2
Heater Control	On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (optional)
Related Products	-

\*Design and specifications are subject to change without prior notice.