

## Specification:

Model number		M-HD-360B
Screen	Display	5 inch TFT-LCD screen, 800*480 resolution
Video Mode	CVBS	1 channel BNC input, NTSC/PAL (Auto adapt)
		PTZ control, RS485 control, Baud 600-115200bps, compatible with more than 30 protocols such as PELCO-D/P, Samsung, Panasonic etc
	HD Coaxial test	8MP TVI camera test, 3840 x 2160P 12.5/15 FPS, UTC control / call OSD menu
		8MP CVI camera test, 3840 x 2160P 12.5/15 FPS, UTC control / call OSD menu
		8MP AHD test, 3840 x 2160P 15FPS, UTC control / call OSD menu
		8MP EX-SDI, HD-SDI, 3G-SDI, UTC control / call OSD menu
		Auto HD app, auto recognize HD coax camera type and resolution, support coaxial PTZ & call OSD menu
VGA input	1 channel VGA input, support 1920 x 1200P 60FPS. The resolution as follow: 1920 x 1200P 60FPS / 1920x1080P 60FPS / 1792x1344P 60FPS / 1680x 1050P 60FPS / 1600x1200P/900P 60FPS / 1440x900P 60FPS / 1360x768P 60FPS / 1280x1024/960/800/768/720P 60FPS / 1152x870P 60FPS / 1024x768P 60FPS / 800x600P 60FPS / 600x480P 60FPS.	
Power output	DC12V 1A output	DC12V 1A power output, supply temporarily power for the camera
	DC5V 1A output	DC5V 1A power output, support reading USB disk
Cable test	UTP cable test	Test UTP cable connection status and display on the screen. Can detect the near-end, mid-end and far-end fault point of the network cable crystal head
Audio test		1 channel audio signal input, test the audio whether is normal
Power management		Display DC 12V output voltage and power in real time
Data monitor		Captures and analyzes the command data from controlling device, also can send hexadecimal
Power supply		DC 5V 2A
Battery		Built-in 3.7V Lithium ion battery, 5200mAh
Rechargeable		After charging 4 hours, normal working time 6 hours
Operation setting		OSD menu, select your desired language: English, Chinese, Korean, Russian, Italian, French, Polish, Spanish, Japanese, Deutsch, Turkish, Portuguese, Czech etc
Auto off		1-30 (mins)
Working Temperature		-10℃ - +50℃
Working Humidity		30% - 90%
Dimension		183mm x 110mm x 40mm (Tester); 255mm x 140mm x 98mm (Colour box)
Weight		320g (Tester); 1030g (Tester with spare parts, black package, box)