

| Description              |                       | NTSC   | PAL     |
|--------------------------|-----------------------|--|---------|
| Sensor Type              |                       | 2.1 Megapixel SONY STARVIS CMOS Sensor   |         |
| Output Pixels            |                       | 1920 (H) × 1080 (V) = 2.1M pixels  |         |
| Scanning System          |                       | Progressive Scan   |         |
| Lens                     | Filter                | True Day & Night (ICR)   |         |
|                          | Type                  | 2.7~12mm DC IRIS VARIFOCAL 2 Motor LENS (ICR)  |         |
| Video                    | Output                | 1 (BNC 1.0 Vp-p, 75Ω)  |         |
|                          | Resolution            | 1080p30  | 1080p25 |
|                          | Format                | HD-SDI / EX-SDI 1.0 / EX-SDI 2.0 selectable  |         |
| Video Control            | AGC                   | LEVEL 0~10   |         |
|                          | S/N Ratio             | More than 52dB   |         |
|                          | BLC                   | OFF / HLC / BLC / WDR  |         |
|                          | ACE                   | OFF / LOW / MIDDLE / HIGH  |         |
|                          | Min. Illumination     | Color: 0.02Lux@F1.3<br>BW: 0Lux (IR LED On)  |         |
|                          | DNR                   | OFF / LOW / MIDDLE / HIGH  |         |
|                          | Iris Adjustment       | DC / Manual  |         |
|                          | White Balance         | AUTO / AUTOext / PRESET / MANUAL   |         |
|                          | Electric Shutter      | INDOOR / OUTDOOR / INDOOR-ANTI-BLUR /<br>OUTDOOR-ANTI-BLUR / FLICKER / MANUAL (11 Steps) |         |
|                          | OSD Language          | ENG  |         |
|                          | Day&Night             | COLOR / BW / EXTERN / AUTO   |         |
|                          | Defog                 | OFF / ON (AUTO, MANUAL-LOW / MIDDLE / HIGH)  |         |
|                          | Privacy               | OFF / ON (Programmable 10 zones)   |         |
|                          | DSS                   | OFF / AUTO / X2~X32  |         |
|                          | Digital Effect        | OFF / H-MIRROR / V-MIRROR  |         |
|                          | IR LED                | 36 pcs   |         |
|                          | Smart IR              | OFF / ON   |         |
| OSD Control              | OSD Key / CoC (UCC-A) |  |         |
| Input Voltage            |                       | DC48V±10%  |         |
| Power Consumption        |                       | IR OFF : 3W (MAX) / IR ON : 7W (MAX)   |         |
| Operation Temp./Humidity |                       | -10°C ~ +50°C / MAX 90% RH   |         |
| Storage Temp./Humidity   |                       | -20°C ~ +60°C / MAX 90% RH   |         |
| Certification            |                       | KC   |         |

\*제품의 사양은 성능 및 품질 향상을 위해 사전 예고없이 변경 될 수 있습니다  
(Specifications are subject to change without notice for product improvement.)