

CW DETECTION	All U.S. and International Cellular Bands(B71/B12, B13, B14, B26/5, B4/B66, B25, B30)
	Wi-Fi 2401-2473 MHz and 5150-5835 MHz
	Bluetooth & BLE 2402-2480 MHz
DEMODULATION(DUAL-BAND)	2.4 GHz Wi-Fi Channels: 1,2,3,4,5,6,7,8,9,10,11
	5 GHz Wi-Fi Channels: 36,40,44,48,52,56,60,64,100,104,108,112,116,120,124,128,132,136,140,149,153,157,161,165
	Bluetooth Channels: 1-79
	Bluetooth Low Energy Channels: 1-40
MAXIMUM COVERAGE	125 Feet (up to 250 feet using optional DF antenna line of site)
ADDITIONAL DETECTION	BSSID, SSID, Device ID, WPA, WPA2, MAC, Channel/Band #
DYNAMIC RANGE	70 dB
SENSITIVITY	-90 dBm
BANDWIDTH RESOLUTION	4 MHz, 20 MHz
SELECTIVITY REJECTION	Better than 40 dB
RECEIVING MODES	High-speed active scanning
ANTENNAS SUPPORTED	(3) Removable omni-directional SMA antennas(3) Removable DF (Direction Finding) antennas

POWER REQUIREMENTS	110 VAC and 12 VDC internal backup battery (charges from same AC power source)
BACKUP BATTERY RUNTIME	Approximately 2-5 hours (depending upon amount of nearby wireless activity and alerts)
DISPLAY & CONTROL	480 x 272 backlit color TFT with a resistive touch screen
UNIT DIMENSIONS	14.4" x 20" x 4"
WEIGHT	15 lbs. (not including optional DF antennas and stanchion)
PORTS	Dry contacts for external trigger of cameras, DVR and speakers USB for firmware upgrades (cannot be accessed without security key)
ALERTS	12" x 12" color-coded visuals with adjustable brightness and flashing patterns
SOUND	Voice alerts that profile each device with fully adjustable volume control
INCLUDED ACCESSORIES	(3) Omni-directional SMA antennas, power supply, wall mount, (2) keys for security lock
OPTIONAL ACCESSORIES	(3) Direction Finding antennas, stanchion mount